

The automatic rotating-arm stretch wrapping machine meets your needs for high-capacity applications.

For high pallets or products that are risky to handle while the pallet rotates on a turntable, the pallet remains stationary while the rotating arm wraps around the pallet.

Pallets are automatically stretch-wrapped without the need for any personnel.

For products coming from the palletizing line, the stretch film is automatically applied, and after wrapping, the film is automatically cut.

Pallet height: Custom production is available based on your needs.

3 wrapping programs

- 1- Standard wrapping (up-and-down straight wrapping)
- 2- Eco wrapping mode - One-way wrapping
- 3- Applying a top sheet cover

- Rotation diameter: Produced according to request.
- Capable of high-capacity operation
- Photoelectric automatic height adjustment (automatically detects dimensions.)
- Suitable for high-risk and tall pallets
- Bobbin diameter: 250 mm - Bobbin inner diameter: 76 mm
- Inverter configured for soft start.
- Bobbin width: 500 mm
- Feature to set the number of top and bottom wraps
- Power requirements: 220V 50/60Hz 1 ph
- Touchscreen
- Elevator up/down speed adjustment
- Arm rotation speed adjustment
- Manual operation capability
- PLC System
- Color code: RAL 7040-5002
- Made in Turkiye
- Operator panel (Turkish, English)



OPTIONS



Cutting Unit: Binding film and cutting automatically.



Top Press: While wrapping; products that are likely to fall are fixed by pressure from the piston or motor, preventing possible damage.



RIP Application: By turning the stretch film into a rope, it prevents the risk of overturning the products.

Top Sheet Cover:

A plastic film is automatically applied to the top of the pallet to protect it from external factors.