

AUTOMATIC TURNTABLE STRETCH WRAPPING MACHINE

Pallets are automatically stretch-wrapped without the need for any personnel.

Stretch film is automatically applied to products coming from the palletizing line, and after wrapping, the film is automatically cut.

Tower height: 2500 mm – Optional 3000mm-3500mm

Wrapping program

- 1- Standard wrapping (up-and-down straight wrapping)
 - 2- Eco wrapping mode - One-way wrapping
 - 3- Application of top protective cover
- Table diameter:
1650 mm - Optional 1800 mm - 2000 mm
 - PLC system
 - Touchscreen
 - Lift speed adjustment
 - Table rotation speed adjustment
 - An inverter is configured for soft start.
 - Manual operation capability
 - Bobbin diameter: 250 mm
 - Bobbin inner diameter: 76 mm
 - Bobbin width: 500 mm
 - Color code: RAL 7040-5002
 - Photoelectric automatic height adjustment (automatically detects dimensions.)
 - Pallet top-bottom tou number setting feature
 - Power requirements: 220V 50/60Hz 1 ph
 - Made in Turkiye
 - Operator panel (Turkish, English)



OPTIONS



Cutting Unit: Binding film and cutting automatically.



Top Press: While wrapping; products that are likely to fall are fixed by pressure from the piston or motor, preventing possible damage.



RIP Application: By turning the stretch film into a rope, it prevents the risk of overturning the products.

Top Sheet Cover:

A plastic film is automatically applied to the top of the pallet to protect it from external factors.