

Machine height: 2500 mm (Ops. 3000 mm)

Max. pallet dimensions:

(Y) 2200 mm Opt: 2700 mm x (G) 1200 mm x 1200 mm

- Table diameter: 1650mm. Optionally: 1800-2000mm
- Loading ramp and motorized pre-stretch system included
- PLC System – Touch Screen
- Loading capacity max.1500 kg

4 wrapping programs;

- 1- Standart wrapping (Up & Down)
 - 2- Only wrapping up
 - 3- While wrapping, waiting on the top of the pallet to cover sheet etc. for upper protection.
 - 4- The one-way version of the third program that only goes up
- Elevator up-down speed and turntable speed adjustment
 - Automatic pallet height detection by photocell
 - Starting and standart tension rate adjustment
 - Adjustable the wrapping tour numbers
 - Film roll diameter 250mm, width 500mm
 - Inverter for soft start and stop
 - Colour: Ral 7040-5002 (Gray-Blue)
 - Power requirement: 220V 50Hz 1 ph, Installed power: 1,4 kW
 - Operator panel in 6 different languages
(Turkish, English, German, French,
Spanish, Arabic)
 - CE certification, Made in Turkiye



STRETCH MACHINE OPTIONS



Cutting Unit: Binding film and cutting automatically.



Top Press: While wrapping; products that are likely to fall are fixed by pressure from the piston or motor, preventing possible damage.



Pre-stretch with motor:
Using pre-stretch with motor, from 50% up to 400% savings using Super Power stretch film



RIP Application: By turning the stretch film into a rope, it prevents the risk of overturning the products.